



Portal Login

Contact Us



United States (English)

Search

INDUSTRIES

PRODUCTS

SUPPORT & DOWNLOADS

TRAINING & SERVICES

RESOURCES

ABOUT EFI

Home > Products > Inkjet Printing and Proofing > VUTEk Superwide Printers > VUTEk High-Volume Printers > *EFI VUTEk GS2000LX Pro*

# EFI VUTEk GS2000LX Pro

How to Buy

Versatile Hybrid Flatbed/Roll-fed Printers

EFI VUTEk LX3 Pro

EFI VUTEk GS2000

**EFI VUTEk GS2000LX Pro**

EFI VUTEk GS2000LX Pro with UltraDrop Technology

EFI VUTEk GS3250

EFI VUTEk GS3250LX Pro

EFI VUTEk GS3250LX Pro with UltraDrop Technology

EFI VUTEk HS125 Pro

## Offer more with production level LED printing

Designed to drive productivity, the two-meter EFI™ VUTEk® GS2000LX Pro LED printer gives you the ability to print on thinner and specialty substrates while lowering costs.



Overview   Features   Specifications   Applications   Resources   Support

### Media/Handling

- Handles rigid and sheeted media up to 80 in. (2 m) wide and up to 2 in. (5.08 cm) thick
- Optional extension table with casters and small depth extension table

### Productivity

- Fast-4™: 2,000 ft<sup>2</sup>/hr (186 m<sup>2</sup>/hr)
  - Production up to 45 – 4'x8' (1.2m x 2.4m) boards per hour
- Eight-color plus white: 1,000 ft<sup>2</sup>/hr (93 m<sup>2</sup>/hr)
  - Production up to 24 – 4'x8' (1.2m x 2.4m) boards per hour

### Environmental considerations

- Compressed Air: 100-150 psi maximum at 12 cf/m—dry air only (not included)
- Fully enclosed design for operator safety and environmental considerations
- Temperature: 68° F to 86° F (20° C to 30° C)
- Humidity: 40% to 80% (noncondensing)
- Machine weight: 5,050 lbs. (2,291 kg)
- Height: 66" (167.6 cm)
- Width: 202" (513.08 cm)
- Depth: 63" (160 cm) without tables; 163" (414 cm) with tables
  - + 5" (12.7 cm) unwinder
  - + 5" (12.7 cm) rewinder

### Featured Videos

[EFI Inkjet Product Line](#)  
[VUTEk White Ink Technology](#)

### EFI VUTEk 3M MCS Warranty



3M™ MCS™ Warranty

[Learn More](#)

### Fiery proServer

- Electrical: 3-Phase, 60 amps @ 200–230 volt supply or 30 amp @400-460 volt supply

**Genuine EFI Inks**

- Supplied in 5.0-liter containers
- Expanded gamut CMYK pigments for world-class pantone matching
- EFI pigment dispersions ensure optimized size and concentration for best-in-class ink stability

**EFI Fiery proServer**

- Optimized for use with the EFI Fiery proServer
- Bidirectional communication capability between the Fiery
- Fiery XF software and printer allows back communication of audit information on every print job
- Powerful production tools such as nesting, step and repeat, scaling, cropping and tiling
- Advanced ICC color management for reliable color, quality output and proofing-quality color

**Enhanced Service Program (ESP)**

- EFI's industry-leading service and support program for your printer, Fiery proServer hardware and Fiery XF software
- Thirteen months of Essential coverage, with 24-business-hour (three-business-day) response
- Eligible for upgrade to:
  - Critical: Providing eight-business-hour (one-business-day) response
  - ProActive: Providing 16-business-hour (two-business-day) response



Other Products of Interest

- [Fiery proServer](#)
- [Fiery XF](#)
- [Digital StoreFront](#)
- [Pace Print MIS Software](#)
- [Genuine EFI Inks](#)

Terms of Use | Privacy | Investor Relations | Careers | Contact Us

© 2016 Electronics For Imaging, Inc. All Rights Reserved.

Follow us     