



Spire III Series – Thermal Wide Format Professional Laminators



The GBC Spire III 44T and 64T take lamination to a new level. With modern, industrial design and extensive feature sets, the Spire III 44T & 64T provide cost effective, high quality lamination unsurpassed by others in their class. All steel construction promises long-term durability and reliability while the built-in sophistication ensures a professionally finished job – thermal or cold – every time.

Running at a maximum speed of 20 feet per minute with 4" heat rollers, the Spire III machines are fast and retain heat better for longer runs. Even beginners will find the Spire III easy-to-use with a user-friendly control panel and auto grip, easy-load supply shafts for no-hassle film loading. Designed with an eye for increasing versatility, a 2" mounting gap allows for mounting of thicker substrates while optional unwinds and rewinds and roll-to-roll capabilities can be easily added later.

Features and benefits

Easy to Use

- Simple, intuitive control panel with LED pressure readout
- Hand crank for opening and closing rollers provides an infinite choice of settings
- Deep feed table makes feeding larger sheets effortless

Productive

- 20ft/min laminating capability
- Foot pedal for hands-free operation
- Larger diameter heat rollers retain heat for longer runs

Versatile

- Designed to create most applications regardless of whether they require thermal or PSA films
- Up to 44" or 64" wide laminating and mounting capabilities
- Increased mounting gap to mount to thicker substrates
- Larger film rolls can load easily on the machine
- Independently controlled upper and lower heat rollers allow for running multiple thermal film gauges and PSA films concurrently
- Optional unwinds and rewinds can be added as applications expand to allow for roll-to-roll capabilities

Durable

- All steel construction for lasting performance



Spire III Series – Thermal Wide Format Professional Laminators

Spire III 44T and 64T Specifications

Item Number	44T – 1737174 64T – 1737175
Maximum Laminating Width	44T – 44" 64T – 64"
Core Diameter	3"
Unwinds/Rewinds	Top - 1 Unwind, 1 Rewind Bottom Front - 1 Unwind, 1 Optional Unwind Top Rear - Optional Rewind Lower Rear - Optional Rewind
Maximum Speed	20ft/min
Maximum Temperature	300° F
Heat Roller Diameter	4"
Independent Heater Controls	Yes
Maximum Mounting Gap	2"
Type of Roller Pressure Adjust.	Infinite crank handle with scale indicator for gap & LED pressure readout
Protective Shield (heat rollers)	Photo eye
Roll-to-Roll Capabilities	Optional
Foot Switch	Yes
Types of Supply Shafts	2 Drop-In Autogrip 1 Drop-In Multicore Media Additional Autogrip and Multicore Media Available
Maximum Film Outside Diameter	10"
Digital Display with mechanical push-button Control Panel	Yes
Front Feed Table	Swing-up, Front and Rear table Idler bars - Optional
Drive System	Sprocket & chain User adjustable pull roller clutch
Cooling Fans	Yes
Idler Chill Roller Bar	Yes
Weight, lbs.	Net: 44T – 691 lbs., 64T – 902 lbs. Shipping: 44T – 880 lbs., 64T – 1,166 lbs.
Dimensions: in. (w x l x h)	Net: 44T – 61.5" x 31.5" x 55.9", 64T – 81.2" x 31.5" x 55.9" Shipping: 44T – 62.2" x 32.1" x 62.2", 64T – 81.9" x 32.1" x 62.2"
Voltage/Amperage	44T – 220 VAC, 24 Amps (NEMA 6-30) 64T – 220 VAC, 28 Amps (NEMA 6-50)

Films

For best results use high-quality GBC® films and mounting adhesives

- Octiva® Thermal Films
- Octiva® Lo-Melt Thermal Films
- Arctic® Pressure Sensitive Films
- Arctic® Pressure Sensitive Mounting Adhesives
- AccuShield®

Applications

- Trade show graphics
- Posters
- Rigid displays
- Backlit displays
- Window displays
- Banners
- Flexible displays
- Window graphics

