



## Acuity Advance Select

### *Acuity Advance Select*

The Acuity Advance Select UV flatbed inkjet printer from Fujifilm delivers all of the market leading image quality, performance and reliability benefits of the Acuity Advance series. The Acuity Advance Select has 8 channels offering extended color, white and clear ink options. These options provide a wider selection of color options to further enhance productivity and add versatility for a wide range of applications.

#### Key highlights

- ▶ In-line double strike white capability
- ▶ In line value added clear ink option
- ▶ Two new high quality production print modes
- ▶ Controlled print-bed vacuum strength through additional zoning capability
- ▶ New job handling capability and throughput
- ▶ Improved image quality uniformity through print-bed mapping



## Specifications

|                        |               | Select  | Select X2   |
|------------------------|---------------|---|---|
| Print technology       |               | Piezo Drive   |   |
| Rigid media            |               | Maximum media size: 49.2" x 98.4" x 1.89"<br>Maximum print area: 49.6" x 98.8"  | Maximum media size: 98.4" x 120" x 1.9"<br>Maximum print area: 98.8" x 120.4" |
| Roll media             |               | Roll Width: 35.4" - 86.6"<br>Maximum print width: 86.2"<br>Maximum roll weight: 110 lbs                                   |   |
| Ink                    | Configuration | C/M/Y/K/W/V<br>Fujifilm Uvjet KO/KI series  |   |
|                        | Package       | 2L pouch (C,M,Y,K)<br>1L pouch (W, V)   |   |
| Ink type               |               | Fujifilm Uvjet KO and KI series UV curable inks   |   |
| Print head             |               | Toshiba Tec CE-2 greyscale, variable drop 6pl – 42pl<br>8 printheads  |   |
| Number of nozzles      |               | 636 nozzles/color - single color per head   |   |
| Printing resolution    |               | Image quality is equivalent to 1,200dpi resolution or higher  |   |
| Connectivity           |               | 100/1000BASE-T  |   |
| Operating temperatures |               | 18-30°C<br>30-70% RH Non-Condensing   |   |
| Media type             |               | Targeted at rigid PVC, PETG, acrylic, foam board,<br>With roll unit - self adhesive PVC, banner material, PET, and paper. |   |
| RIP options            |               | ColorGATE Productionserver7 Fujifilm Edition  |   |
| Power requirements     |               | 50Hz, 200 to 240 VAC, Single Phase, 16A<br>60Hz, 208 to 240 VAC, Single Phase, 16A<br>Two AC power circuits               |   |
| Dimensions (W) x (D)   |               | Printer only: 183" x 78"<br>Printer & Roll media option: 183" x 90"   | Printer only: 183" x 150"<br>Printer & Roll media option: 183" x 162"         |
| Weight                 |               | Printer only: 1047 lbs<br>Printer & Roll media option: 1433 lbs   | Printer only: 2425 lbs<br>Printer & Roll media option: 2811 lbs               |

## Print Modes and Speeds

| Mode               | Select                  |                         | Select X2               |                         |
|--------------------|-------------------------|-------------------------|-------------------------|-------------------------|
|                    | Flatbed                 | Roll-to-Roll            | Flatbed                 | Roll-to-Roll            |
| Express            | 353 ft <sup>2</sup> /hr | 276 ft <sup>2</sup> /hr | 368 ft <sup>2</sup> /hr | 276 ft <sup>2</sup> /hr |
| Production Squared | 264 ft <sup>2</sup> /hr | 202 ft <sup>2</sup> /hr | 272 ft <sup>2</sup> /hr | 202 ft <sup>2</sup> /hr |
| Production         | 219 ft <sup>2</sup> /hr | 182 ft <sup>2</sup> /hr | 226 ft <sup>2</sup> /hr | 182 ft <sup>2</sup> /hr |
| Production Smooth  | 219 ft <sup>2</sup> /hr | 182 ft <sup>2</sup> /hr | 226 ft <sup>2</sup> /hr | 182 ft <sup>2</sup> /hr |
| Quality            | 151 ft <sup>2</sup> /hr | 125 ft <sup>2</sup> /hr | 155 ft <sup>2</sup> /hr | 125 ft <sup>2</sup> /hr |
| White 2 layer      | 75 ft <sup>2</sup> /hr  | 62 ft <sup>2</sup> /hr  | 77 ft <sup>2</sup> /hr  | 62 ft <sup>2</sup> /hr  |
| White 3 Layer      | 50 ft <sup>2</sup> /hr  | 42 ft <sup>2</sup> /hr  | 52 ft <sup>2</sup> /hr  | 41 ft <sup>2</sup> /hr  |

# FUJIFILM

Fujifilm North America Corporation, Graphic Systems Division

Phone: 913.342.4060 • Email: [contactgraphics@fujifilm.com](mailto:contactgraphics@fujifilm.com) • Web: [www.fujifilmgraphics.com](http://www.fujifilmgraphics.com)